

QDX SERIES

SUBMERSIBLE PUMP



Model	Rated Power		Q.Max	H.Max	Rated voltage	Frequency	Pipesize
	KW	HP	m ³ /h	m	V	HZ	Inch
QDX1.5-16-0.37	0.37	0.5	6	17	220	50	1"
QDX6-10-0.37	0.37	0.5	12	12	220	50	1.5"
QDX3-20-0.55(F)	0.55	0.75	7.3	20	220	50	1"
QDX1.5-32-0.75(F)	0.75	1	6	33	220	50	1"
QDX10-16-0.75(F)	0.75	1	15	20	220	50	2"
QDX7-18-0.75(F)	0.75	1	16.8	18.5	220	50	1.5"
QDX15-10-0.75(F)	0.75	1	18	15.5	220	50	2"
QDX6-24-1.1(F)	1.1	1.5	12	25	220	50	1.5"
QDX6-26-1.1(F)	1.1	1.5	15	27	220	50	1.5"
QDX15-15-1.1(F)	1.1	1.5	24	18	220	50	2"
QDX30-6-1.1(F)	1.1	1.5	30	15	220	50	3"
QDX40-7-1.1(F)	1.1	1.5	48	10.5	220	50	3"
QDX6-33-1.5(F)	1.5	2	15	35.5	220	50	1.5"
QDX15-18-1.5(F)	1.5	2	30	20	220	50	2"
QDX40-7-1.5(F)	1.5	2	40	16	220	50	3"
QDX40-9-1.5(F)	1.5	2	54	13.5	220	50	3"

**Please note that model F is with float, model without float will not have F



THUAN HIEP THANH COMPANY LIMITED
 21/20/77 và 21/20/79 , Le Cong Phep Street, An Lac
 Ward, Binh Tan District, Ho Chi Minh City

WQD SERIES

SEWAGE SUBMERSIBLE PUMP



This series of pumps are widely used in agriculture, architecture, mine, environment protection and industry, such as drainage slurry, waste water, which contained short fibre, wastepaper, sand, and so on.



Model	Rated Power		Q.Max m³/h	H.Max m	Rated voltage V	Frequency HZ	Pipesize Inch
	KW	HP					
WQD7-7-0.55QG(F)	0.55	0.75	7	7	220	50	2"
WQD7-10-0.75QG(F)	0.75	1	18	14	220	50	2"
WQD7-15-1.1QG(F)	1.1	1.5	21	16.5	220	50	2"
WQD6-22-1.5QG(F)	1.5	2	27	28	220	50	2"
WQD9-22-2.2QG(F)	2.2	3	38	22	220	50	2"
WQD7-7-0.55(F)	0.55	0.75	7	7	220	50	2"
WQD7-10-0.75(F)	0.75	1	18	14	220	50	2"
WQD7-15-1.1(F)	1.1	1.5	21	16.5	220	50	2"

V/VDF SERIES

SEWAGE SUBMERSIBLE PUMP





V180F/V250F



V750DF



V750F



Model	Rated Power		Q.Max m³/h	H.Max m	Rated voltage V	Frequency HZ	Pipesize inch
	KW	HP					
V180	0.18	0.245	7.8	6.5	220	50	1.25"
V250	0.25	0.3	9	7.5	220	50	1.25"
V450	0.45	0.6	12	8.5	220	50	2"
V750	0.75	1	18	14	220	50	2"
V1100	1.1	1.5	21	16.5	220	50	2"
V1500	1.5	2	27	17	220	50	2"
V2200	2.2	3	42	17	220	50	4"

**Please note that model F is with float, model without float will not have F